Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Novel Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT Model identifier: 82270787-02 Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light No source (CLS): Colour-tuneable light source: Yes Envelope: - High luminance light source: No Anti-glare shield: No Dimmable: Yes Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°)
Model identifier: 82270787-02 Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (corother electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Yes Envelope: - High luminance light source: No No Dimmable: Yes Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) LED Non-directional or NDLS Non-directional or NDLS No Dimmable: Yes Envelope: - Feneral product parameters Fenergy efficiency F class 100 Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light No source (CLS): Colour-tuneable light source: High luminance light source: No Anti-glare shield: No Dimmable: Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) LED Non-directional: No Nonected light No Dimmable: Yes Product parameters Parameter Value Fenergy efficiency class 1 Sphere (360°) temperature, rounded to the nearest 100 K, or the range of
Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light No source (CLS): Colour-tuneable light source: High luminance light source: No No Dimmable: Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) LED Module No Non-directional or directional or directional: No No Dimmable: Yes Fenery efficiency F class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: No Anti-glare shield: Parameter Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) LED Module Venue Fenvelope: - Product parameter Yes Product parameters Fenergy efficiency class Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of
(or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: High luminance light source: No Anti-glare shield: Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) NO Dimmable: Yes Product parameter Value Parameter Value Fenergy efficiency class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: High luminance light source: No Anti-glare shield: Parameter Parameter Value Parameters Fenergy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) No Dimmable: Yes Product parameters Value Parameter Value Fenergy efficiency F class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Source (CLS): Colour-tuneable light source: High luminance light source: No Anti-glare shield: Product parameters Parameter Value Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Source (CLS): Envelope: - Character Product parameters Value Parameter Value Parameter Value Fenergy efficiency or class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
High luminance light source: Anti-glare shield: No Dimmable: Yes Product parameters Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) No Dimmable: Yes Yes Energy efficiency class Energy efficiency class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Anti-glare shield: No Dimmable: Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) No Dimmable: Yes Yes Parameter Value Fenergy efficiency class Correlated colour 30006500 temperature, rounded to the nearest 100 K, or the range of
Parameter Value Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Product parameters Value Parameter Value F Correlated colour Sphere (360°) temperature, rounded to the nearest 100 K, or the range of
Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Parameter Value Parameter Value Parameter Value Correlateds Correlated colour Sphere (360°) temperature, rounded to the nearest 100 K, or the range of
General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) General product parameters: Energy efficiency class 440 in Correlated colour temperature, rounded to the nearest 100 K, or the range of
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Energy efficiency class 30006500 temperature, rounded to the nearest 100 K, or the range of
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Useful luminous flux (фuse), and a sphere (360°) Sphere (360°) Sphere (360°) temperature, and to the nearest 100 K, or the range of
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Sphere (360°) temperature, rounded to the nearest 100 K, or the range of
temperatures, rounded to the nearest 100 K, that can be set
On-mode power (P _{on}), 5,0 Standby power (P _{sb}), 0,12 expressed in W and rounded to the second decimal
Networked standby power (P _{net}) - Colour rendering index, rounded to the second decimal the nearest integer, or the range of CRI-values that can be set
Outer Height 1 Spectral power See image
dimensions Width 20 distribution in the in last page
without Depth 224

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity	0,431	
		coordinates (x and y)	0,399	
Parameters for LED and OLED light sources:				
R9 colour rendering index valu	ie 7	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

