## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Novel

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271400-02

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	3	Energy efficiency class	F		
dicating if it refe a sphere (360 <sup>o</sup> )	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	300 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	120	Spectral power dis-	See image		
sions without	Width	75	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	2	range 250 nm to 800 nm, at full-load	Dago 1 / 2		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

