## **Product Information Sheet**

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

Height

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Importabtei	lung, Römerstraße	39, 4600 Wels, AT		
Model identifier: 82271550				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
	Product para	meters		
Parameter	Value	Parameter	Value	
	General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P <sub>on</sub> ), expressed in W	10,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,30	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or	90	

332

6

2

the range of CRI-val-

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

the

tribution

ues that can be set

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	80	Survival factor	1,00		
the lumen maintenance factor	0,95				

(a)'-': not applicable; (b)'-': not applicable;

## Spectral power distribution at 4000K

