Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

91

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271331-01

Τv	pe	of	light	soui	ce:
. ,	P-	•			···

Type of light source.					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on-	24	Energy efficiency	Е		

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consumpti mode (kWh/1000 up to the nearest in	h), rounded	24	Energy efficiency class	E	
Useful luminous flu dicating if it refers t a sphere (360º), in (120º) or in a narro	to the flux in a wide cone	2 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		24,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
sions without W	eight 'idth epth	129 360 27	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page	

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,445 0,405		
Parameters for LED and OLED I	ight sources:				
R9 colour rendering index value	9 0	Survival factor	0,90		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	t	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

