



CARABEL

FR44623BCH

Bulbs: 100W MED.

[DRAWING 1]


ASSEMBLY INSTRUCTIONS

Assembly of this fixture will be accomplished by assembling the main body of the fixture, installing the mounting hardware to the junction box, making all necessary electrical connections and then hanging the fixture.

SAFETY WARNING: Read wiring and grounding instructions [FRIS 18] and any additional directions. Turn power supply off during installation. If new wiring is required, consult a qualified electrician or local authorities for code requirements.

STEP 1

- 1 Slip center stem (g) along wire and thread it into coupler (h) approximately 3/8", now slip center column (5) over center stem (g).
- 2 Slip loop (i) along wire and thread onto end of center stem (g) to secure center column (5).
- 3 Slip shade (1) into the cage assembly (2). Making sure the inside edge of the shade (a) are located by the 4 tabs (b) on the lower cage arms (c).
- 4 Lay acrylic lens (3) onto tabs (b).
- 5 Remove ball knobs with studs (4) from top of center column (5).
- 6 Attach top of scroll arms (6) to the center column assembly (5), using ball knob studs (4).
- 7 Remove screw (7) from tabs (e) located at the top of cage assembly (2).
- 8 Slip center column (5) with attached scroll arms (6) into cage assembly (2) aligning the holes (d) in the end of the scrolls, with the holes (e) located on tabs in the cage assembly.
- 9 Slip screws (7) through the hole (d) in the end of scroll (6) and thread it into tab (e), repeat for remaining scrolls, center column (5) is now secured to the cage (2).
- 10 Thread bottom finial (8) onto threaded stem (f) located at the bottom of the fixture.
- 11 Fixture can now be lamped accordingly.



STEP 2 Refer to Hanging Instruction Sheet [FRIS19] to hang fixture and complete assembly.



FREDRICK RAMOND

ESTABLISHED 1965

800.421.3517 WWW.FREDRICKRAMOND.COM

12.1.09