## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Yu Yang

Supplier's address: Yu Yang Deutschland GmbH , Vahrenwalder Str. 205, 30165 Hannover, DE

## Model identifier: 2835 LED Strip 60LEDs/M-1

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Stecker		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

**Product parameters** 

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consump mode (kWh/1000 up to the nearest	0 h), rounded	2	Energy efficiency class	F		
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	ers to the flux )º), in a wide	230 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode po expressed in W	wer (P <sub>on</sub> ),	2,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	83		
Outer	Height	1	Spectral power	See image		
dimensions	Width	10	distribution in the	in last page		

Claim of equivalent power(a)-If yes, equivalent power (W)-Claim of equivalent power(a)-If yes, equivalent power (W)-Chromaticity coordinates (x and y)0,438 coordinates (x and y)0,438 coordinates (x and y)Parameters for LED and OLED light sources:R9 colour rendering index value9Survival factor0,90the lumen maintenance factor0,96Image: Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3">Colspan="3"	withoutDeptseparateControl gear,lightingControl partsandnon-lightingControl parts,ifany(millimetre)	h	500	range 250 nm to 800 nm, at full-load			
Parameters for LED and OLED light sources:coordinates (x and y)R9 colour rendering index value9Survival factor0,90	Claim of equivalent po	ower <sup>(a)</sup>	-		-		
R9 colour rendering index value9Survival factor0,90				,	0,438		
	Parameters for LED and OLED light sources:						
the lumen maintenance factor 0,96	R9 colour rendering ir	ndex value	9	Survival factor	0,90		
	the lumen maintenance factor		0,96				

(a)'-' : not applicable;

(b)'-' : not applicable;

