Product Information Sheet

Depth

separate con-

trol gear, light-

control

ing

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

Supplier's name or trade mark: Dieter Knoll Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT											
							Model identifie	r: 92300001-02			
							Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS							
Light source cap-type		LED Module									
(or other electric interface)											
Mains or non-mains:		NMLS	Connected light source (CLS):	No							
Colour-tuneable light source:		Yes	Envelope:	-							
High luminance	light source:	No									
Anti-glare shield	l:	No	Dimmable:	Yes							
		Product para	meters								
Parameter		Value	Parameter	Value							
		General product p	parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	G							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		225 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 3 000							
On-mode power (P _{on}), expressed in W		2,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	83							
Outer dimen-	Height	87	Spectral power dis-	See image							
sions without	Width	2	tribution in the	in last page							

87

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,459			
		nates (x and y)	0,407			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	13	Survival factor	1,00			
the lumen maintenance factor	0,98					

(a)'-': not applicable; (b)'-': not applicable;

