Product Information Sheet

ing

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOAILD REGOI	LATION (LO) 2013/2	.013 With regard to energ	gy labelling of light							
Supplier's name or trade mark: Xora Supplier's address: Importableilung, Römerstraße 39, 4600 Wels, AT Model identifier: 40620037-01											
							Type of light so	urce:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		LED Module									
(or other electric interface)											
Mains or non-mains:		NMLS	Connected light source (CLS):	No							
Colour-tuneable light source:		No	Envelope:	-							
High luminance light source:		No									
Anti-glare shield:		No	Dimmable:	No							
		Product para	meters								
Parameter		Value	Parameter	Value							
		General product p	parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		20	Energy efficiency class	F							
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000							
On-mode power (P _{on}), expressed in W		19,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82							
Outer dimen-	Height	14	Spectral power dis-	See image							
sions without	Width	181	tribution in the	in last page							
separate control gear, light	Depth	167	range 250 nm to 800 nm, at full-load								

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	141			
		Chromaticity coordi-	0,440			
		nates (x and y)	0,399			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	82	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

