## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: Boxxx							
Supplier's address: Import, Wiesenstraße 46, 4600 Wels, AT							
Model identifie	er: 82271135-10						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		E27					
(or other electr	ic interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		12	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 020 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W		11,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84			
Outer	Height	124	Spectral power	See image			
dimensions without	Width	60	distribution in the	in last page			
without	Depth	60					

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		Yes	If yes, equivalent power (W)	80			
			Chromaticity	0,426			
			coordinates (x and y)	0,392			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		18	Survival factor	0,90			
the lumen maintenance factor		0,93					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,99	Colour consistency in McAdam ellipses	0			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		0,4	Stroboscopic effect metric (SVM)	0,0			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

