## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271532-01

_	•			
Type	Λt	light	COLL	rca.
IVDE	VI.	HEILL	SOU	LC.

Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap	o-type	LED Module		
(or other electri	ic interface)			
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	High luminance light source:			
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	1
Parameter		Value	Parameter	Value
		General product p	parameters:	
- ·	nption in on- 00 h), rounded st integer	24	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	2 000	Spectral power dis-	See image
sions without	Width	5	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	1	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime-					
tre)  Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,440 0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	5	Survival factor	1,00		
the lumen maintenance factor	0,95				
Parameters for LED and OLED m	ains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

