



A	A1	B	C
240/9.45"	220/8.66"	48/1.89"	100/3.94"
D	E	F	G
60/2.4"	130/5.12"	ø1500/59.1"	745/29.33"

Befestigung	Decke
Spannung (V)	220V-240V
Hertz	50/60Hz
Klasse	I
IP	20
FSC Madera	Si
Material der Struktur	Stahl
Material der Ventilatorblätter	Holz
Oberflächenbehandlung der Struktur	Mattes Weiß
RAL/Pantone Gehäuse	RAL 9016
Flügeloberfläche	Eiche
Motortyp	DC
Ventilatorleistung (W)	5-7-11-17-24-35
U/min	67-88-106-122-140-159
Airflow (CFM)	2215-3121-4050-4592-5208-59852215-3121-4050-4592-5208-59852215-3121-4050-4592-5208-59852215-3121-4050-4592-5208-59852215-3121-4050-4592-5208-5985
Anzahl der Flügel	3
Wendbare Flügel	Nein
Umkehrfunktion	Ja
Geeignet für schräge Decken	Ja
Maximale Neigung (°)	12
Art der Steuerung enthalten	Fernbedienung mit Timer
Art der Bedienung des Ventilators	TUYA APP + COMANDO POR VOZ ALEXA/GOOGLE HOME
Lüfter	1-4-8h
Programmierstunden	26
Rohrdurchmesser	26
Optionales Stangenmodell	Universal 26mm

Installationsanleitung



Verwandte Zubehörteile



DC Remote Control	
Referenz	33987
Spannung (V)	100V-240V
Hertz	50/60Hz
IP	20
Material der Struktur	ABS + Glas



DC Remote Control	
Referenz	33988
Spannung (V)	100V-240V
Hertz	50/60Hz



DC Remote Control Accessory	
Referenz	34303



DC Remote Control Accessory	
Referenz	34304



Taki Ligth Kit

Referenz

3L003



Klim L Ligth Kit

Referenz

3L023

