Product Information Sheet

pressed in W

Outer dimen-

sions without

separate con-

trol gear, light-

control

imal

ing

Networked standby

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

power

240

560

560

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:		20 4000 14/1		
Supplier's address: Importabteil	ung, Römerstraße 3	39, 4600 Wels, AT		
Model identifier: 85820042-02				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
	Product para	meters		
Parameter	Value	Parameter	Value	
	General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	43	Energy efficiency class	Е	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	5 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), ex-	43,0	Standby power (P _{sb}),	0,00	

expressed in W and rounded to the sec-

Colour rendering in-

ond decimal

80

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,435		
		nates (x and y)	0,400		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	3	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,2		

(a)'-': not applicable; (b)'-': not applicable;

