

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Dieter Knoll

**Supplier's address:** Importabteilung, Römerstraße 39, 4600 Wels, AT

**Model identifier:** 82271741-02

## Type of light source:

|                                                     |            |                                 |      |
|-----------------------------------------------------|------------|---------------------------------|------|
| Lighting technology used:                           | LED        | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | LED Module |                                 |      |
| Mains or non-mains:                                 | MLS        | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No         | Envelope:                       | -    |
| High luminance light source:                        | No         |                                 |      |
| Anti-glare shield:                                  | No         | Dimmable:                       | Yes  |


## Product parameters

| Parameter                                                                                                                                             | Value                  | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |                        |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 42                     | Energy efficiency class                                                                                                                                    | E                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 5 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 42,0                   | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,50                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without separate control gear, lighting control                                                                                      | Height                 | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                       | Width                  |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth                  |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|---------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)                                                               |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    | If yes, equivalent power (W)          | -              |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)    | 0,321<br>0,343 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                       |                |  |
| R9 colour rendering index value                                                                                         | 5    | Survival factor                       | 1,00           |  |
| the lumen maintenance factor                                                                                            | 0,96 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,90 | Colour consistency in McAdam ellipses | 5              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,1  | Stroboscopic effect metric (SVM)      | 0,1            |  |

(a) '-': not applicable;

(b) '-': not applicable;



Model placed on the Union market from 28/02/2025.



**EPREL registration number:** 2254691

<https://eprel.ec.europa.eu/qr/2254691>

**Supplier:** BDSK Handels GmbH & Co. KG (Importer)

**Website:** [www.xxxlgroup.com](http://www.xxxlgroup.com)

**Customer care service:**

**Name:** Importabteilung

**Website:**

**Email:** [EPREL-info@xxxlgroup.com](mailto:EPREL-info@xxxlgroup.com)

**Phone:** +4350111500949

**Address:**

Römerstraße 39  
4600 Wels  
Austria