Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Novel Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT Model identifier: 82271386-03 Type of light source:										
							Lighting technology used:	LED	Non-directional or directional:	NDLS
							Light source cap-type	LED Module		
							(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes							
Colour-tuneable light source:	Yes	Envelope:	-							
High luminance light source:	No									
Anti-glare shield:	No	Dimmable:	No							
Product parameters										
Parameter	Value	Parameter	Value							

rign iuminance	light source:	INO					
Anti-glare shield	d:	No	Dimmable:	No			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
0,	mption in on- 00 h), rounded st integer	5	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), iners to the flux in, in a wide cone arrow cone (90º)	450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50			
(P _{net}) for CLS, 6	tandby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimensions without separate control gear, lighting control	Height	900	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image			
	Width	12		in last page			
	Depth	2					

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,315			
		nates (x and y)	0,338			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,80	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,3			

(a)'-': not applicable; (b)'-': not applicable;

