## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Glandor

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

## Model identifier: 8181846-02

## Type of light source:

| Lighting technology used:     | LED        | Non-directional or directional: | NDLS |  |  |
|-------------------------------|------------|---------------------------------|------|--|--|
| Light source cap-type         | LED Module |                                 |      |  |  |
| (or other electric interface) |            |                                 |      |  |  |
| Mains or non-mains:           | MLS        | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No         | Envelope:                       | -    |  |  |
| High luminance light source:  | No         |                                 |      |  |  |
| Anti-glare shield:            | No         | Dimmable:                       | Yes  |  |  |
| Product parameters            |            |                                 |      |  |  |

| Product parameters   |   |                              |  |              |  |  |
|--|---|------------------------------|--|--------------|--|--|
| Parameter  |   | Value                        | Parameter  | Value        |  |  |
| General product parameters:  |   |                              |  |              |  |  |
| •.   | nption in on-<br>00 h), rounded<br>st integer                                   | 50                           | Energy efficiency<br>class   | E            |  |  |
| dicating if it refe<br>a sphere (360 <sup>o</sup> )                | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>nrow cone (90º) | 5 520 in Wide<br>cone (120°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 27006000     |  |  |
| On-mode pow<br>pressed in W  | ver (P <sub>on</sub> ), ex-   | 50,0                         | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,40         |  |  |
| (P <sub>net</sub> ) for CLS, e                                     | andby power<br>expressed in W<br>the second dec-                                | -                            | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |
| Outer dimen-   | Height  | 445                          | Spectral power dis-  | See image    |  |  |
| sions without<br>separate con-<br>trol gear, light-<br>ing control | Width<br>Depth  | 445<br>1                     | tribution in the<br>range 250 nm to 800<br>nm, at full-load  | in last page |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)   |      |  |                |  |  |  |
|--|------|--|----------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)             | -              |  |  |  |
|  |      | Chromaticity coordi-<br>nates (x and y)  | 0,441<br>0,412 |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |                |  |  |  |
| R9 colour rendering index value  | 4    | Survival factor                          | 0,90           |  |  |  |
| the lumen maintenance factor   | 0,96 |  |                |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |                |  |  |  |
| displacement factor (cos φ1)   | 0,85 | Colour consistency<br>in McAdam ellipses | 6              |  |  |  |
| Claims that an LED light source<br>replaces a fluorescent light<br>source without integrated bal-<br>last of a particular wattage. | _(b) | If yes then replace-<br>ment claim (W)   | -              |  |  |  |
| Flicker metric (Pst LM)  | 1,0  | Stroboscopic effect<br>metric (SVM)      | 0,4            |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

