Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Novel

Supplier's address: -

Model identifier: 82271027-01

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	No		
Product parameters					

		i iouuci para	inclus			
Parameter		Value	Parameter	Value		
General product parameters:						
0,	mption in on- 000 h), rounded est integer	61	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (φuse), efers to the flux 60º), in a wide in a narrow cone	6 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode expressed in W	oower (P _{on}),	61,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	2	Spectral power	See image		
	Width	10	distribution in the	in last page		
	Depth	3 713				
	1	1	1	Seite 1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,435 0,395			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

