Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Ambiente		
Supplier's address:	Importabteilung, Römerstraße 39, 4600 Wels, AT	

Model	identifier	82271328-01
ivioaei	identiner:	0///13/0-01

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	3 Uui C	c.

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

Lighting technology used:	LED	Non-directional or directional:	NDLS		
11.11	II.	an cononal.			
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
	Product para	meters			
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	34	Energy efficiency class	E		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W	34,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen- Height	5 100	Spectral power dis-	See image		

8

1

tribution in the

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime-					
tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,372		
		nates (x and y)	0,369		
Parameters for LED and OLED	light sources:				
R9 colour rendering index valu	e 4	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED	Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	it	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,8		

(a)'-': not applicable; (b)'-': not applicable;

