Product Information Sheet

On-mode power (Pon), ex-

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

power

pressed in W

Outer dimen-

sions without

separate con-

trol gear, light-

control

imal

ing

Networked standby

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Importabteilu	ıng, Römerstraße	39, 4600 Wels, AT	
Model identifier: 60330003-04			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
·	Product para	imeters	
Parameter	Value	Parameter	Value
	General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	49	Energy efficiency class	Е
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	5 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000

49,0

2

10

2 700

Standby power (P_{sb}),

expressed in W and

rounded to the sec-

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

the

ond decimal

tribution

0,00

80

See image in last page

parts and non- lighting con- trol parts, if any (millime-					
tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,440		
		nates (x and y)	0,401		
Parameters for LED and OLED lig	ght sources:				
R9 colour rendering index value	7	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

