Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLOAILD KLOOI	-ATION (LO) 2019/2	2015 with regard to ener	gy labelling of light		
Supplier's name	e or trade mark:	Novel				
Supplier's address: Importableilung, Römerstraße 39, 4600 Wels, AT						
Model identifie	er: 40240040-03					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		LED Module				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para		T -		
Parameter		Value	Parameter	Value		
		General product	<u> </u>	T _		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		11	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		11,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	335	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	8 1	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,432			
		nates (x and y)	0,398			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

