## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271279-01

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Ulabeth a ka aba a ba a la accessa de	LED	Niam alterational and	NDLC			
Lighting technology used:	LED	Non-directional or	NDLS			
		directional:				
Light source cap-type	LED Module					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light	No			
		source (CLS):				
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						
Parameter	Value	Parameter	Value			

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neares		24	Energy efficiency class	Е	
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	3 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimensions without separate control gear, lighting control	Height Width Depth	2 160 10 2	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,431			
		nates (x and y)	0,393			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED m	ains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)'-': not applicable; (b)'-': not applicable;

