Product Information Sheet

On-mode power

Networked standby

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

pressed in W

Outer dimen-

sions without

separate con-

trol gear, light-

control

imal

ing

 (P_{on}) ,

power

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade marks	Povvv			
Supplier's name or trade mark:		20. 4600 144 47		
Supplier's address: Importabtei	lung, Romerstraße :	39, 4600 Wels, Al		
Model identifier: 82271535-09				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Bulb E27			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
	Product para	meters		
Parameter	Value	Parameter	Value	
	General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	E	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 020 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K,	3 000	

8,0

60

60

106

that can be set

ond decimal

tribution

Standby power (P_{sb}),

expressed in W and

rounded to the sec-

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

the

0,00

80

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
Parameters for LED and OLED lig	tht sources:		
R9 colour rendering index value	10	Survival factor	1,00
the lumen maintenance factor	0,93		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

