## **Product Information Sheet**

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name	e or trade mark:	Novel				
Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT						
Model identifie	r: 82271021-01					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type (or other electric interface)		LED Module				
Mains or non-mains:		MLS	Connected light source (CLS):	Yes		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	Yes		
		Product para	meters			
Parameter		Value	Parameter	Value		
		General product	parameters:			
Energy consummode (kWh/10 up to the nearest	00 h), rounded	24	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), ex- pressed in W		24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer dimen-	Height	1 640	Spectral power dis-	See image		
sions without	Width	8	tribution in the	in last page		

1

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,442 0,401			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	7	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)'-': not applicable; (b)'-': not applicable;

