## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Sources				
Supplier's name or trade mark:	Ambiente			
Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT  Model identifier: 60330003-05				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
	Product para	meters		
Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	49	Energy efficiency class	E	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	5 700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P <sub>on</sub> ), expressed in W	49,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-	80	

2

10

2 700

Outer dimen-

sions without

separate con-

trol gear, light-

control

ing

Height

Width

Depth

ues that can be set

tribution

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

See image

in last page

parts and non- lighting con- trol parts, if any (millime-				
tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,440	
		nates (x and y)	0,401	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	7	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;

