Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Dieter Knoll
Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT
Model identifier: 31700002-01

Type of light source: Lighting technology used: Non-directional LED **NDLS** directional: Light source cap-type LED Module (or other electric interface) Mains or non-mains: **NMLS** Connected light No source (CLS): Colour-tuneable light source: No Envelope: High luminance light source: No

Colour-tuneable light source: No Envelope: High luminance light source: No Dimmable: Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in Sphere (360°) Connected light No Envelope: Value Parameter Value Parameter Value Fenergy efficiency class Correlated colour 2700...6500 temperature.

mode (kWh/1000 h), rounded up to the nearest integer			class	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	4 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode power (P _{on}), expressed in W		41,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	628	Spectral power dis-	See image
sions without	Width	11	tribution in the	in last page
separate control gear, lighting control	Depth	1	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,318			
		nates (x and y)	0,340			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	48	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

