Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Novel

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271277-01

Type of light source:

Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	_
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

	Froduct parameters							
Parameter		Value	Parameter	Value				
General product parameters:								
• ·	nption in on- 00 h), rounded st integer	30	Energy efficiency class	E				
dicating if it refe a sphere (360°),	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	3 900 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000				
On-mode pow pressed in W	ver (P _{on}), ex-	30,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00				
(P_{net}) for CLS, ϵ	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80				
Outer dimen-	Height	880	Spectral power dis-	See image				
sions without separate con- trol gear, light- ing control	Width Depth	8	tribution in the range 250 nm to 800 nm, at full-load	in last page				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,383 0,381			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	1,00			
the lumen maintenance factor	0,97					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	_			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;

