Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Luminex

Supplier's address: LUMINEX s.r.o., Petra Rezka 10, 140 00 Prag, CZ

Model identifier: L 71389

Networked standby power

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

_	•			
Tyna	Ot.	lioht	sour	CD.
IVDC	O.	IIGIIL	30ui	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G 9		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	1
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	D
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode power (P _{on}), expressed in W	7,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
		1	00

75

19

19

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

Spectral power dis-

tribution in the

range 250 nm to 800

nm, at full-load

80

See image in last page

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,440 0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	10	Survival factor	0,98		
the lumen maintenance factor	0,90				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,56	Colour consistency in McAdam ellipses	3		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

