



1. If you are placing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the ceiling.
2. Screw top threaded pipe 3 complete turns into the flat side of installation bracket and lock in place with hex nut.
3. Fasten the installation bracket to the ceiling using the two screws supplied.

4. Electrical connections: Follow enclosed supplement installation instruction for connection.

5. Place crown thru top threaded pipe so that it sits flush against ceiling. Be sure all wires are inside pan. Secure crown to ceiling by fastening lock washer and coupler onto top threaded pipe.
Note: Coupler must turn at least 3 times, if it does not you must remove coupler and lengthen threaded pipe accordingly.

6. Install bottom threaded pipe into coupler.

7. Install bulbs (not included). See relamping label located at socket area for type and maximum allowed wattage.

8. Flush Mounts With Cap + Finial:

Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with hex nut; if provided. Do not over tighten. Then slide cap up and secure with finial.

Flush Mounts With Only Finial-Recessed At Top:

Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with hex nut. Do not over tighten. Then secure with finial.

Flush Mounts With Only Finial-Flat Top:

Place shade thru center pipe so that top rim of glass checks properly into bottom of crown. Secure glass shade with finial.