## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	sources						
Supplier's name or trade mark: Novel							
Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT							
Model identifie	r: 82271014-01						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		LED Module					
(or other electric interface)							
Mains or non-mains:		NMLS	Connected light source (CLS):	Yes			
Colour-tuneable	e light source:	No	Envelope:	-			
High luminance	light source:	No					
Anti-glare shield:		No	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		19	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P <sub>on</sub> ), expressed in W		19,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,26	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	3	Spectral power	See image			
dimensions	Width	280	distribution in the	in last page			
without	Depth	280		 			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,460			
		coordinates (x and y)	0,417			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

