



**IMPORTANT:
TURN OFF POWER AT MAIN FUSE OR
CIRCUIT BREAKER BOX BEFORE
STARTING INSTALLATION**

1. Carefully remove all parts from box and remove wrappings. NOTE: DO NOT YET REMOVE WRAPPING SURROUNDING THE GLASS SHADE. Carefully lay parts on a non-abrasive surface and identify all parts before assembly. Bulb not included.
2. Screw center pipe onto fixture plate while removing any slack in wires in between parts.
3. Install arms:
 - A. Install three out of four arms onto the ring by fastening bottom section with lock washer and hex head screws. See illustration for correct position of arms.
 - B. Take the glass shade and gently slip through until it locates at center inside of ring.
 - C. Install last arm onto the ring.
 - D. Install upper section of arms onto fixture plate by fastening with small lock washer and small hex nut.
 - E. Use enclosed hex key to tighten hex head screws.
4. Carefully remove wrapping from glass shade.
5. Install threaded stud into finial. Then slip the threaded stud through cap and bottom hole of glass shade. Lock all together by fastening with flat washer, lock washer, and hex nut from above. Do not over tighten.
6. Install light bulb (not included). See relamping label located at socket area for type and maximum allowed wattage.
7. Follow enclosed supplement installation instructions for electrical and fixture installation onto house outlet box. If you do not have an outlet box at desired location to attach the fixture than hire a qualified electrician to create one