

Technical data

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Midea	
Model name / identifier	60L07
Annual Energy Consumption (AEC_{hood})	53,0 kWh/year
Energy efficiency class	C
A+ (most efficient) to F (least efficient)	C
Energy efficiency index (EEL_{hood})	81,5
Fluid Dynamic Efficiency (FDE_{hood})	10,7
Fluid Dynamic Efficiency class	E
A (most efficient) to G (least efficient)	E
Lighting Efficiency (LE_{hood})	38
Lighting Efficiency class	A
A (most efficient) to G (least efficient)	A
Grease Filtering Efficiency	86,2
Grease Filtering Efficiency class	B
A (most efficient) to G (least efficient)	B
Airflow at best efficiency point : Exterior / Recirculation	245,3 m ³ /h
Air flow (min. speed) : Exterior / Recirculation	284,8 m ³ /h
Air flow (max. speed) : Exterior / Recirculation	439,9 m ³ /h
Air flow (intensive or boost setting) : Exterior / Recirculation	/
Max. air flow (Q_{max}) : Exterior / Recirculation	439,9 m ³ /h
Air pressure at best efficiency point	140 Pa
Airborne acoustical A-weighted sound power emissions (min. speed)	56 dB
Airborne acoustical A-weighted sound power emissions (max. speed)	63 dB
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	/
Electrical power input at best efficiency point	89,1 W
Power consumption in off mode (P_o)	/
Power consumption in standby mode (P_s)	/
Nominal power of lighting system	1,5 W
Average illumination of the lighting system on the cooking surface	51 lux